

	SCT 2000 shower change table, coated most cover electrically height	
Product	SCT 2000 shower change table, coated mesh cover, electrically height adjustable	
Item number	R8478000	
Colour	VVS: 777544480  NRF: 7501961  EAN: 5708590318523  HMI: 88223  NBS: N13:40,375  White	
Product description	SCT 2000 shower change table, powered, height adjustable 700 mm; from 300 mm - 1000 mm, with wired hand control Foldable. Incl. safety rail and water collection tray with integrated outlet. Outer measurements 900 mm x 1800 mm. Excl. mounting kit. See Technical datasheet (pdf) for information on fixings suitable for various wall types. Replaces R8468.  SCT 2000 shower change table, powered, height adjustable 700 mm; from 300 mm - 1000 mm, with wired hand control Foldable. Incl. safety rail and water collection tray with integrated outlet. Outer measurements 900 mm x 1800 mm. Materials: Powder-lacquered stainless steel, coated mesh cover and polystyrene. Excl. mounting kit.	
Adjustability	Height adjustable	
Adjustment height	700 mm	
Product capacity	Maximum load: 175 kg. When the table is loaded with 175 kg, each mounting bolt supports 23 kg This product has been tested statically with a load of 440 kg as the IEC 60601- standard requires testing with safety factor 2.5.	
Speed	Speed up mm: 15 mm/s Speed down mm: 20 mm/s	
Noise level	48 dB	
Materials	Powder-laquered stainless steel, mesh cover (PVC-coated for extra durability) and polystyrene.	



Product	SCT 2000 shower change table, coated mesh cover, electrically height adjustable	
Item number	R8478000	
Ergonomy	Pressalit offers a range of high quality, fixed or power adjusted shower and changing tables designed to provide a stable platform suitable for changing adults and children in a variety of settings: schools, day care centres, institutions, hospitals and private homes.  The 2000 series shower and changing tables has a low start position, to make transfers to the bench easier. The washable, perforated mesh cover lets the water pass through to the water collection tray underneath.  The flexibility of the shower and changing table provides for optimal working conditions for the carer as well as a high level of comfort and safety for the user.	
Features	A water collection tray with integrated water outlet prevents water from splashing on carers or the floor. The flexible hose attached to the centre mounted outlet of the water collection tray, can be connected to either an outlet in the floor or on the wall. The integrated gas cylinders enable the table to be folded out of the way when not in use to maximise floor space in front of the unit.  Electric with wired hand control – the red buttons clearly indicate "Up" and "Down". The wired hand control comes with a holder for fitting to the wall.  The stretcher of the table is very easy to clean, and the stretcher cover can be unzipped for washing or easy replacement.	
Mains connection (V)	230	
Actuator (motor)	LA31 Careline, (Linak), 6000 N, IPX6	
Control box	CB9 Careline, (Linak), IPX6	
Wired remote control	HB3 (Linak), IP66	
Power consumption (maximum load)	Power consumption by maximum load: 70 W Power consumption by standby: 2 W	
Warranty	Pressalit makes a commitment to remedy material and manufacturing defects for a period of three years from the invoicing date. NOTICE If the product is installed in an atmosphere heavy in salt or chloride, the warranty will be reduced from the normal 3 years to 1 year. Salt and chloride have a corrosive effect on the products components and will cause a decrease in the life expectancy of the product. The damaging effects can, however, be reduced if the product is showered with tap water on a daily basis.	



Product	SCT 2000 shower change table, coated mesh cover, electrically height adjustable
Item number	R8478000
Cleaning	Showering and changing tables 1000 & 2000. The product is to be cleaned with hot water or a mild soapy cleaning agent. Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged.  The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container.  DISINFECTANTS: Clinimax Difficil-S Erisan OXY+  NON-DISINFECTANTS: Suma Star free D1 Taski 100 Taski 200  The product must be wiped down with a soft rag wrung out in clear water immediately after cleaning, as some materials may otherwise be discolored and stained, and the surface coating may deteriorate.
Declaration of conformity	This product complies with the requirements of Council Directive 93/42/EEC concerning medical devices, as last amended by Council Directive 2007/47/EC of 5 September 2007. It also complies with all relevant requirements in the Council Directive 2006/42/EC (of 17 May 2006) on machinery and the Council Directive 2011/65/EC on RoHS.



Product		
Item	numbe	

SCT 2000 shower change table, coated mesh cover, electrically height adjustable

R8478000

#### Installation in different wall types

amorone wan typoo	
Concrete >B25  V8608 - Mounting kit, 6 coach screws Ø10 x 70 - plugs SX12.  To be ordered separately.	
Solid Brick >= Mz12  V8608 - Mounting kit, 6 coach screws Ø10 x 70 - plugs SX12.  To be ordered separately.	
Solid Sand Lime Brick >= HIz12  V8608 - Mounting kit, 6 coach screws Ø10 x 70 - plugs SX12.  To be ordered separately.	
Aerated Concrete P4  V8658 - Mounting kit, 6 coach screws Ø10 x 70 - plugs GB14.  To be ordered separately.	
Drywall (2 x 12,5 mm) water-resistant, re-enforced with wood  V8608 - Mounting kit, 6 coach screws Ø10 x 70 - plugs  SX12. NB! Plugs are not needed.  To be ordered separately.	



Product Item number	SCT 2000 shower change table, coated mesh cover, electrically height adjustable R8478000
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with 22 mm plywood  Wall fasteners (6 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (2 mm)  Wall fasteners (6 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.
	Drywall (2 x 12,5 mm) water-resistant  Mounting in this wall type is not recommended - risk of fatal injury to persons and walls.
	idda injury to persons and waits.

It is the responsibility of the installer to ensure that suitable wall fasteners are used.







#### www.pressalit.com

Pressalit A/S
Pressalitvej 1
DK-8680 Ry
Tel.: +45 8788 8788
Fax: +45 8788 8789
E-mail: pressalit@pressalit.com